



ISOGEN 42

impermeabilizzante cementizio elastico .

Line

GENERALKOLL

Function

Bi-component elastic cement mortar for protecting and proofing concrete, swimming pool foundation, balconies, roofs, terraces, etc

Materials

concrete, swimming pool foundation, balconies, roofs, terraces

How to use

PREPARING THE BACKGROUND: The foundations must be compact, solid, clean and free from any oily or greasy substances that can compromise the adhesion. Surfaces / foundations to be treated must be preventively wet.

PREPARING THE MIXTURE: Pour "component B" (liquid) in a clean container/can of adequate capacity to contain the whole mixture and after pour the powder content of the bag "component A"

Mix the two components by means of a drill, working at low rpm, equipped by suitable mixing tool till to obtain a homogeneous mortar/mass without lumps.

APPLICATION: Spread the obtained mortar by flat putty knife or roller or suitable spraying device. By only one coat it is possible to make a layer till to 3 mm. thickness.

In case of foundation particularly under stress it is suggested to apply the first coat and insert a fibreglass net.

Packaging

A: paper bag of 25 kg. net

B: plastic can of 9,5 kg. net

Characteristics

A:GREY POWDER
B:WHITISH LIQUID

Important

COMP A):CANNOT STAND THE HUMIDITY

COMP.B):CANNOT STAND THE FROST

12 months in dry room, into the original and closed packaging, at temperature not lower than 0°C (32°F) nor exceeding 35°C (95°F).

Industria Chimica General

Via Rep. S. Marino, 8 - 41122 Modena, Italy - Tel. +39 059.450.991/059.450.978 - Fax +39 059.450.615

Stabilimento Generalkoll - Via Uralita, 7 - 44012 Zerbinato di Bondeno - FE, Italy

Web site: www.generalchemical.it