



## **GENERALKOLL GK 104 BIANCO C2FT**

adesivo cementizio a presa rapida per marmo, granito e pietra naturali.

### **Line**

GENERALKOLL

### **Function**

Laying floors and walls of marble, granite and natural stones both indoor and outdoor. Gluing by points of fiberglass insulating panels, polystyrene foam, polyurethane foam. Overlay of ceramic on ceramic and stone on stone

### **Materials**

Laying floors and walls of marble, granite and natural stones both indoor and outdoor

### **How to use**

Mix 25 kg of GK 104 with 6-6.5 litres of clean water, possibly using a low-speed mixer, until to obtain a homogeneous mixture without clots.

Leave the mixture to stand for about 5 minutes then mix again, at least 30 seconds, before using. The prepared mixture, mixed again immediately before using, has a shelf-life of about 1-2 hours (according to environmental conditions: temperature, ventilation, etc.).

### **Packaging**

multi-layer polythene-lined paper bags.  
Bags of 25 kg. each

### **Characteristics**

white powder

MIXTURE SHELF-LIFE 1-2 hours

APPLICATION TEMPERATURE between 5°C and 35°C (41°F and 95°F)

OPEN TIME 10 minutes

## **Important**

ALWAYS EFFECT A PRELIMINARY TEST BEFORE THE APPLICATION

---

**Industria Chimica General**

Via Rep. S. Marino, 8 - 41122 Modena, Italy - Tel. +39 059.450.991/059.450.978 - Fax +39 059.450.615  
Stabilimento Generalkoll - Via Uralita, 7 - 44012 Zerbinato di Bondeno - FE, Italy  
Web site: [www.generalchemical.it](http://www.generalchemical.it)