



## **MABEL CERA**

cera antiscivolo a base acquosa.

### **Line**

PROTECTIVE

### **Function**

SLIP-PROOF PROTECTIVE AND POLISHING. SUITABLE FOR ALL POLISHED SURFACES TO BE PROTECTED WITH A FILM OF WAX WITH STRONG SLIP-PROOF CHARACTERISTICS

### **Materials**

SPECIALLY FORMULATED FOR MARBLES, GRANITES, POLISHED NATURAL STONE. CAN ALSO BE APPLIED TO WOOD AND PLASTIC.

### **How to use**

APPLICATION:

1. Spread a film of wax on the surface to be treated using the sprayer provided or a cotton cloth, with rotary movements and passing over the same areas several times.

2. Make sure the wax is applied uniformly over the entire surface.

Wait a few minutes (2-5) to allow the wax to properly absorb and attach to the floor. Wait another 5-10 minutes to allow it to dry well and then proceed to polish.

POLISHING:

Rub and polish with a clean cloth until eventual marks or streaks disappear.

NOTE:

For a stronger antislip effect apply one or two coats more according to the absorption capacity of the surface and the required effect

### **Packaging**

L.1-5

### **Characteristics**

WATER-BASED WAX AND RESIN EMULSION.

---

### **Important**

A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION.  
USE ONLY ORIGINAL CONTAINERS; NEVER POUR THE PRODUCT INTO OTHER METAL OR GLASS  
CONTAINERS.

---

**Industria Chimica General**

Via Rep. S. Marino, 8 - 41122 Modena, Italy - Tel. +39 059.450.991/059.450.978 - Fax +39 059.450.615

Stabilimento Generalkoll - Via Uralita, 7 - 44012 Zerbinato di Bondeno - FE, Italy

Web site: [www.generalchemical.it](http://www.generalchemical.it)