



DIAMANTINA

polvere per rinnovare il marmo.

Line

HOUSE

Function

Removal of imperfections and small marks from the polished surface

Materials

Soft marbles such as: Portugal pink, Carrara, Thassos, etc

How to use

Pour 30-60 gr. (1-2 spoons) of product every square meter of surface. The polishing operation must be effected by a polishing machine with low rotating speed (1000-2000 rpm) equipped with a merinos-wool felt. Put a little water on the powder to obtain a mixture of doughy consistence and, putting the felt of the polishing machine on the paste compound, start with the polishing operation. Work only few square meters each time.

The friction causes the water evaporation and with the drying of the floor the marble get shining. A coating of product remains on the floor. By a cotton cloth remove it from a small part of the surface to check and verify the shine grade. If necessary, repeat the operation.

Once the polishing operation is over, remove from the surface the residual coating of product by washing with Neutrex diluted 1:5 (1 part of Neutrex and 5 parts of water) and after rinse with clear water. After drying (24-48 hours) the treatment of the floor by Imperston Natura is suggested to preserve the shine and to avoid the seepage of stain of oils, foodstuffs dirt, juices, fruit etc

Packaging

0.5KG

Characteristics

Polishing mineral powders

Important

On wide surfaces the best results are obtained by using heavy professional machines able to develop a high friction. It is possible anyway the use of normal single-brush machines, eventually ballasted to make them more heavy, The use of single-brush machine is particularly suitable for the restoration and the renewal of the shine on old floors. A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION
