



RAIN STOP

water repellent , antismog, antimould

Line

PROTECTION

Function

IMPREGNATOR, WATER-REPELLENT, ANTISMOG, ANTIMOULD PROTECTING AGENT.[]
Makes the surface water repellent without impeding the natural transpiration of the material. Doesn't get shining and doesn't change the surface appearance. Water runs off without penetrating the surface. It doesn't anyway protect against acid substances.[]

[]

Materials

MARBLE, GRANITE, NATURAL STONES, TERRACOTTA, BRICKS, CONCRETE, TERRAZZO and AGGLOMERATES etc. FOR FLOOR AND WALL APPLICATION.[]

[]

How to use

Apply the undiluted product to the surface allowing to penetrate according to the surface porosity, but avoid the product dries on the surface. If the product dries on surface can appear spots or/and cloudy zones; remove any excess with a cotton rag to avoid spotting or clouding (cotton rag may be dampened with mineral turpentine). After drying, a second coat may be applied.[]

On particularly delicate surfaces, slight modifications in color may occur. The user must conduct on-site testing to verify, after drying, the effect and to determine the compatibility of the product with the material to be treated.[]

[]

Packaging

250ml[]

L.1-5-10-25

Characteristics

Contains solvents and silicon resins. Active ingredients approx. 9

Important

Solvent-based product: inflammable. Wear impermeable gloves and apply in well ventilated areas and eventually wear a solvent-proof mask. For more information, see product label or product Safety Data Sheet.A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION.[]

USE ONLY ORIGINAL CONTAINERS;NEVER POUR THE PRODUCT INTO OTHER METAL OR GLASS CONTAINERS[]

Industria Chimica General

Via Rep. S. Marino, 8 - 41122 Modena, Italy - Tel. +39 059.450.991/059.450.978 - Fax +39 059.450.615
Stabilimento Generalkoll - Via Uralita, 7 - 44012 Zerbinate di Bondeno - FE, Italy
Web site: www.generalchemical.it