



POLIEP

special adhesive also for humid or wet materials

Line

POLIEPOXY

Function

SPECIAL ADHESIVE ALSO FOR HUMID OR WET MATERIALS

Materials

MARBLE, GRANITE, STONES, IRON, WOOD ALSO FOR HUMID OR WET MATERIALS

How to use

100 grams of POLIEP + 2 grams of paste hardener. For best results mix 2% to 3% of the catalyst (dibenzoyl peroxide) with the adhesive. The paste formula makes easy to measure. A homogeneous mixing will facilitate uniform catalysis. The catalysis rate is effected by temperature and by the proportion/quantity of catalyst. An excess of hardener/catalyst will increase the hardening speed, but weakens the adhesive seal.

Packaging

L.1

Characteristics

Available in standard colours: STRAW/BEIGE. Possibility of other colours upon request. □

- higher total content of resins; □
- longer working time (better wettability also on less porous supports: iron, etc.); □
- longer self-life and stability; □
- low odour and styrene controlled emission thanks to the presence of appropriated inhibitors; □
- better polishing result thanks to the presence of suitable and studied mineral □

Important

POLIEPÂ® WITH STYRENE. ALWAYS EFFECT A PRELIMINARY TEST BEFORE THE APPLICATION □
□