



TERMOGEN 77

cement mortar for insulating systems

Line

GENERALKOLL

Function

Pre-mixed cement mortar, mono-component, based on Portland cement, for gluing and smoothing thermo insulating panels and insulating plaster systems

Materials

Suitable for gluing thermo-insulating panels in general (expanded/extruded polystyrene, expanded polyurethane) directly on the plaster, masonry or concrete. □

Suitable for smoothing insulating panels with interposed fibreglass reinforcing net, resistant to alkali, indoor and outdoor walls ("over coat" insulating system) □

How to use

The surface must be greasy substances or/and dirt free. Eventual traces of oil, grease, wax, etc. must be preventively removed. To each 25 kg. bag of TERMOGen 77 add 7 to 7.5 liters of clear water and mix by hand or, better, by mechanic stirrer working at low rpm equipped with suitable mixing helical tool till to obtain a homogeneous and lumps free texture. To glue panels, apply the texture "by strips" and place the panels in staggered way taking care to fix them by suitable anchoring (mechanical or chemical anchors). Smooth the surface and sink into the applied texture a fibreglass net resistant to alkali.

Packaging

Paper bags of 25 kg. each

Important

TERMOGen 77 must be used at the original state (as it is) without adding any kind of alien material. Store in dry place, into the original sealed packaging, for a period not exceeding 12