



COLORFUGA

Cement based filler, sealant, for joints, available in many colour and 0-2, 2-12, 12-20 mm

Line

GENERALKOLL

Function

Cement based filler, sealant, for joints

Materials

Sealing of floors and walls covered with ceramic tiles, mosaic, marble, granite, natural stone, terracotta, terrazzo, marble agglomerates

How to use

Mix 5 kg. of COLORFUGA together with 1-1.2 liter of clean water, possibly by using a stirrer with low rpm, till to obtain a homogeneous and lump-free paste considering that a mixture for joints can be more fluid of a mixture for laying floor or/and wall tiles.

Let the mixture "mature" about 5 minutes long and then, before using it, mix again at least 30 seconds. The mixture prepared like this, subject to mixing before the application, has a self-life of 1 hour about

Packaging

multilayer polythene bags of 5 kg. each, put in carton boxes of 4 bags each.

Characteristics

available in 24 colours

MIXTURE SELF-LIFE 1 hour abt.

APPLICATION TEMPERATURE from +5°C to +35°C (41°F to 95°F)

OPEN TIME at 20°C (68°F) and 60% R.H. max 30'

REQUIRED PRODUCT CALCULATION

A= TILE LENGTH (in mm)

B= TILE WIDTH (in mm)

C= TILE THICKNESS (in mm)

D= JOINT WIDTH TO BE FILLED (in mm)

$[(A+B)/(A \times B)] \times C \times D \times 1,6 = \text{REQUIRED PRODUCT in kg/mq}$