



LATEX 2000

latex for building industry

Line

GENERALKOLL

Function

Aqueous emulsion of special elastic resins that highly resistant to water and alkali. • Improves the workability of cement mixtures and performs a significant adhesion increase

Materials

CEMENT POWDER ADHESIVES and CEMENT MORTARS FOR BUILDING INDUSTRY

How to use

For CEMENT POWDER ADHESIVES and JOINT FILLING MORTARS/ADHESIVESEVERY 25 kg. OF CEMENT POWDER ADHESIVE ADD 7 - 8 LITERS of LATEX 2000 AND MIX BY USING A LOW RPM STIRRER TILL TO OBTAIN A HOMOGENEOUS AND LUMP-FREE PASTE. BEFORE USING, LEAVE THE MIXTURE TO STAND FOR AT LEAST 5 MINUTES. THEN MIX AGAIN FOR 30 SECONDS BEFORE TO USE. □

□
for CEMENT MORTARS and REPAIR MORTARS□
PARTIALLY REPLACE THE WATER USUALLY USED FOR THE CEMENT MORTAR WITH 40%-60% OF LATEX 2000 (in the most difficult cases the water can be replaced in higher percentage or completely). PRE-MIX THE WATER and LATEX 2000 AND THEN MIX WITH THE SAND AND THE CEMENT

Packaging

L.5-10

Characteristics

ANIONIC MICRONIZED EMULSION

Important

THE PRODUCT CANNOT STAND THE FROST.□
ALWAYS MAKE A PRELIMINARY TEST BEFORE THE FINAL APPLICATION□
□