



POLMAR LUXOR

special polishing powder only for marble to use on damp with traditonal machines

Line

POLISHING POWDERS

Function

Polishing of marble and agglomerates

Materials

Marble and agglomerates .Also hard marbles like:Green Alpi, Grey Carnico, Black Portoro

How to use

Grind and clean the surface and remove any mechanical residue: nails, brick dust, crushed stone, etc. Apply 30 to 60 grams of product per square meter of surface (abt. 1-2 oz/y²), sprinkling the powder over surface and place the machine's felt pad on top of the powder, then dampen the area till to obtain a milky/creamy consistency. Work 1 - 2 square meters by time. Friction will cause the water evaporation; add water to maintain the product creamy. With the drying the marble will be polished. Verify the glossy effect with a window-wiper. A patina of product will remain on the surface; on a small area use a rag to remove the surface patina and check the level of gloss underneath and repeat the procedure if desired. Once the polishing phase is completed on the entire surface to be treated, remove the residual patina by washing with Neutrex diluted in a 1:5 water solution. Rinse with clear water. After drying (24 to 48 hours) apply the antinfiltrant Imperston to preserve the polish and avoid staining from oil, food, etc.

Packaging

Kg 1-5-10

Characteristics

With natural resins

Important

ALWAYS EFFECT A PRELIMINARY TEST BEFORE THE APPLICATION