



TECHNICAL DATA SHEET
PRODUCT

AGGLOPOLISH PLUS

**SPECIAL POLISHING POWDER
for MARBLE and SYNTHETIC MARBLE AGGLOMERATES**

SPECIAL POLISHING POWDER FOR SYNTHETIC MARBLE AGGLOMERATES

Thanks to the use of abrasive substances of high-level combined with sealant, synthetic and crystallizing substances and natural resins, AGGLOPOLISH PLUS performs a perfect chemical-mechanical polish on marble and synthetic marble agglomerates.

The granular dimensions have been carefully researched, formulated and balanced with abrasive grains consisting of base crystals of medium hardness and natural resins to allow the increase of the shine degree and the restoration of an original glossiness stable in the time.

AGGLOPOLISH PLUS performs a "filling" function of the micro-cavities on the surface for a higher shine.

HOW TO USE

Carefully clean the surface and remove any kind of dirt and solid residuals. Apply 30 to 60 grams of product per square meter (abt. 1-2 tablespoons) and dampen the area by spraying water till to obtain a texture of creamy consistency.

Put the felt/pad of the traditional polishing machine or single-brush machine on the milky/creamy mixture and polish with continuous and constant motion. Work 2-3 square meters time by time for a more homogeneous polishing.

Friction will cause the water evaporation so, eventually, spray water to maintain the product creamy.

With the drying, the surface becomes shining.

Verify the glossy effect and, if necessary, repeat the operation.

After drying (24 hours abt.), to preserve more the shine and to avoid seepages and oily stains, food dirt, etc. the application of an oil and water repellent sealer is suggested.

IMPORTANT

The best results are obtained by using a professional buffing machine able to produce significant friction, but very good results are obtained also with a common single-brush polishing machine that are particularly suitable for restoring and renewing the glossy of old floors or floors became dull because of high pedestrian traffic and wear and tear.

The shine duration strictly depends on the wear and tear of the floor. For a longer life of the shine a light application of wax is suggested; that should be regularly applied during the floor scheduled maintenance.

Effect a preliminary test on a small part of the surface to calculate consumption and measuring according to the kind of material and to verify, after drying, that no polishing halos or marks are on the surface.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

TESTING IN A SMALL, HIDDEN, AREA IS ALWAYS RECOMMENDED BEFORE THE APPLICATION