



# TECHNICAL DATA SHEET

### **COTTOVIVO**

## FINISHING FOR TERRACOTTA FLOORS "OIL FINISHING TRADITION"

Product of easy application completely absorbable by the porous support. It doesn't make film, revives and enhances the colour of the surface and bars the penetration of the stain.

Cottovivo penetrates into the material, tones up the colour and helps in protecting and appreciating the most precious terracotta. It can be applied again periodically according to the desired aesthetic effect.

#### **FUNCTION**

TONING UP OF THE COLOUR AND PROTECTION.

#### LINE

**TERRACOTTA** 

FINISHING TREATMENT

#### **INDICATION**

Revives the colour and gives a good protection to the surface.

Enhances the beauty of the terracotta keeping unchanged the traditional warm look.

#### **MATERIALS**

Terracotta, agglomerates, porous natural stones.

#### **HOW TO USE**

Apply only on dry, clean and greasy substances free surface. Use the product pure as it is and spread it on the surface by a clean cotton cloth. Wait the complete drying of the floor before to walk on it.

#### **TEST**

Before the application, it is suggested to effect a preliminary test on a small part of the surface to determine the compatibility of the product with the material to be treated, the consumption and the drying time and, after drying, the aesthetic result and the protecting level effectively performed.

#### **COMPOSITION**

Contains a mix of oils. Active substance >80%.

#### **TECHNICAL DATA**

The consumption varies according to the porosity of the material. The consumption is considered to be 50 to 120 g/m².

#### **STABILITY**

Contains natural oils. Keep the container closed sheltered from direct sunlight at temperature around 15-25°C (59-77°F). The use within 12-18 months from the purchase date is suggested.

#### **NOTE**

Impregnate carefully the material according to its porosity, but avoid the accumulation of excess of product on the surface. If needed, the product can be removed by **Dekercotto.** 

#### **IMPORTANT**

The material to be treated must be clean and dry.

#### **PACKAGING**

1 L., 5 L.

**LIMITATION OF LIABILITY**The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Since the application of the product is beyond the control of the manufacturer or supplier, our liability for defective products, when verified, is limited to refund of the purchase price.

A PRELIMINARY TEST IS ALWAYS RECOMMENDED BEFORE THE APPLICATION