



UNI EN ISO 9001:2008
Quality System Certified Company



TECHNICAL DATA SHEET

PRODUCT

COTTOFORTE NATURA

**OIL & WATER REPELLENT, REVIVER,
WATER BASED, FOR TERRACOTTA**

The specific formulation of COTTOFORTE NATURA develops a high protecting and anti-infiltration action on every kind of surface of **TERRACOTTA**, while reviving the natural colour with a pleasant and warm effect. Thanks to its very high reviving and protecting action COTTOFORTE NATURA is very used also for treating all kind of **cement agglomerates, bricks and hollow bricks, unglazed gres tiles**.

FUNCTION

SEALER, REVIVER, OIL and WATER REPELLENT, WATER BASED

LINE

TERRACOTTA and BUILDING

PROTECTING SEALER

INDICATION

REVIVES AND ENHANCES THE NATURAL COLOUR OF THE MATERIAL AND PROTECTS AGAINST WATER, OILS AND GREASE. MAKES THE SURFACES ANTI-DIRTY CONTRASTING THE FORMATION OF THE STAINS.

MATERIALS

STUDIED FOR APPLICATION ON TERRACOTTA IT IS SUITABLE FOR BRICKS AND HOLLOW BRICKS, UNGLAZED GRES TILES, CEMENT AGGLOMERATES AS WELL.

INSTRUCTIONS FOR USE

THE SURFACES TO BE TREATED MUST BE DRY (OR STILL HUMID, TOO), CLEAN AND FREE FROM ANY ALIEN SUBSTANCE AND OLD WAXY LAYERS.

SHAKE THE PRODUCT BEFORE APPLYING AND SPREAD EVENLY ONTO THE SURFACE BY A CLEAN COTTON CLOTH OR BY TAMPON.

AFTER SOME MINUTES REMOVE FROM THE SURFACE EVENTUAL NOT ABSORBED EXCESS OF PRODUCT BY USING A COTTON CLOTH.

IN CASE OF VERY POROUS MATERIALS A SECOND APPLICATION MAY BE NEEDED (event to be considered after the product is dried).

USE AT TEMPERATURE BETWEEN 5°C (41°F) AND 35°C (95°F)

TEST

On a small part of the surface effect always a preliminary test to determine the compatibility between the product and the material, the consumption, the drying time and, after drying, the aesthetic effect.

COMPOSITION

CONTAINS ORGANIC POLYMERS, WAXES, WATER

TECHNICAL DATA

DRYING: 45-90 MINUTES (ACCORDING TO THE ENVIRONMENT CONDITIONS AND THE KIND OF MATERIAL).

WALK ON THE SURFACE ONLY WHEN IT IS TOTALLY DRY, SO AFTER SOME HOURS FROM THE APPLICATION; IT IS SUGGESTED TO WAIT AT LEAST 8 TO 12 HOURS AFTER THE APPLICATION BEFORE WALKING ON THE SURFACE THE PROTECTING ACTION IS TOTALLY DEVELOPED AFTER THE FIRST 24 - 48 HOURS.

THE CONSUMPTION IS HIGHLY INFLUENCED BY THE POROSITY OF THE MATERIAL AND VARIES FROM 100 to 200 gr/m².

STABILITY

The product is an aqueous mixture. **CANNOT STAND THE FROST.**

Do not store nor use at temperatures lower than 5°C (41°F) or higher than 35°C (95°F)

NOTE

THE PRODUCT IS A SEALER AND ENHANCES THE COLOUR OF THE TREATED MATERIALS.

IT IS ANYWAY RECOMMENDED TO EFFECT ALWAYS A PRELIMINARY TEST, BEFORE THE FINAL APPLICATION, TO BE WEIGHED AFTER THE MATERIAL IS DRY.



IMPORTANT

APPLY ON CLEAN AND DRY SURFACES (OR STILL HUMID, TOO). WHEN OUTDOOR DO NOT APPLY IN CASE OF FORTHCOMING RAIN.

PACKAGING

1 L., 5 L., 10 L.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

TESTING A SMALL, HIDDEN AREA IS ALWAYS RECOMMENDED BEFORE THE FINAL APPLICATION