



UNI EN ISO 9001:2008
Quality System Certified Company



TECHNICAL DATA SHEET PRODUCT

IMPERSTON

ANTI-STAIN, OIL and WATER REPELLENT PROTECTING AGENT

With its high degree of protection from infiltration, IMPERSTON is the ideal treatment for every type of stone surface (polished or grinded or simply rough), terrazzo, cement agglomerates, building tiles, bricks, unglazed gres, concrete or porcelain gres tiles IMPERSTON is specially recommended for the protection of **marble** and **granite** as the best defence in protecting work surfaces and floors in kitchens and bathrooms. The solvent formula eases the application "by refusal" (apply until no more product is absorbed from the surface) and allows a deep penetration; any way excess of product must be removed to avoid surface build-up after drying.

IMPERSTON works by impregnation and does not form any film on the surface, nor in any way alters the natural colour of the treated materials and it is the ideal product to protect **white** and **delicate marbles**, very light colour or **crystalline marbles** such as CARRARA WHITE, PORTUGAL PINK, ONYX, THASSOS etc.

Furthermore **laboratory tests effected by CNR - Italian National Research Council – state that the materials treated with IMPERSTON, once dried and properly rinsed with clear water, are suitable to the contact with liquid and solid foodstuff at room temperature (as per *certification no. 0041 dated February 28, 2001*).**

IMPERSTON can also be applied as a protective basic foundation for highly absorbent surfaces (such as limestone), to be treated subsequently by a surface application (such as wax).

FUNCTION

IMPREGNATOR, ANTI-STAIN, OIL and WATER REPELLENT, antimog, anti-mould,

PRODUCT LINE

PROTECTION

PROTECTION

PROFESSIONAL

INDICATION

Protects against **water**, **oil** and **grease**: makes the surface stain resistant by preventing the formation of spot. It doesn't anyway protect against acid substances.

MATERIALS

Recommended for all kind of porous materials

HOW TO USE

Apply the undiluted product to clean and dry surface, by a clean cotton cloth or tampon, and let it penetrate. For very porous materials, it may be necessary to repeat the application one or two times more. Do not allow the excess product dries on surface, especially on polished surfaces, as it could be cause of streaking and clouding. The excess of product can be removed with a rag dampened with IMPERSTON or with buffing machine with soft pad. On porous surfaces a second application may be necessary after the first has dried.

TEST

Testing a small, hidden area is recommended before application in order to verify the compatibility between product and material, to determine consumption, drying time and to verify appearance.

COMPOSITION

Contains organic polymers and solvents

TECHNICAL INFORMATION

Dries in 20-60 minutes (depending on ambient conditions and the kind of material).

The protective action has full effect 24 hours after the application.

The consumption will vary according to the porosity and absorption rate of the material and can be considered between 50 and 250 g/m².



NOTE

Solvent based product: apply in well ventilated areas while wearing impermeable gloves.
Keep out from the reach of children
For more information, see product label or product Safety Data Sheet

IMPORTANT

Apply to completely dry and clean surface only.

PACKAGING

250 ml., 750 ml., 5 L., 10 L.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests, the information provided here must be considered as a guideline and not as any form of performance guarantee.
Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION