



UNI EN ISO 9001:2008
Quality System Certified Company



TECHNICAL DATA SHEET

PRODUCT

KD 32

**SEALER / PROTECTOR, REVIVER, AGER
for not polished NATURAL STONES and CONCRETE,
"WET EFFECT"**

It is a self-catalyzing, film making, protective with an extraordinary resistance to the chemical and atmospheric agents. Suitable for indoor use on floors having an intense and high foot-wear traffic, it is ideal for outdoor applications on not polished materials. KD 32 makes a glossy protecting barrier, well adhering, stable during the time and highly reviving of the colour of the treated material. It is largely applied on paving and Venetian-like pavements outdoor placed, on fire-place stone baring the lamp-black penetration and on the industrial paving where bars the penetration of oils and stains.

FUNCTION

PROTECTIVE, BRIGHTENER, HIGHLY REVIVING THE NATURAL COLOURS FOR INTERIOR AND EXTERIOR

LINE

PROTECTION

PROFESSIONAL

INDICATION

Makes the treated surfaces waterproofing and anti-dirt. Revives the natural colours and veining and performs an agreeable old fashion, antiquing, effect.

MATERIALS

ALL KIND OF NOT POLISHED NATURAL STONE AND ABSORBING MATERIALS such as marble, granite, terracotta, travertine, Venetian-like paving, concrete, cement, etc.

HOW TO USE

Apply to dry and clean surfaces with a brush or a cotton cloth. Apply with stroking motion to facilitate the penetration and to avoid build up on the surface. The eventual excess of product must be removed by a cloth before the drying of the product. After drying, a second coat may be applied to intensify the desired effect.

The glossy effect can be limited by rubbing the surface with a cloth impregnated of common denaturated alcohol within the first 6-8 hours from the application.

TEST

Effect always a test on a small part of the surface to determine the compatibility, the consumption, the drying time and, after drying, the aesthetic effect obtained

COMPOSITION

Mixture of solvents and organic compounds (aliphatic isocyanic prepolymers).

TECHNICAL INFORMATION

The consumption is highly influenced by the porosity of the material and is considered to be 100 and 200 g/m². The solvent evaporates in 20 to 60 minutes depending on environmental conditions (temperature, ventilation, humidity, etc.)

The protection is active after the first 24 hours, but the catalysis is completed after 7 (seven) days about.

NOTE

Solvent-based product: apply only in well ventilated areas while wearing impermeable gloves.

Keep out from the reach of children.

For more information about safety see the product label or the Material Safety Data Sheet



IMPORTANT

The product catalyzes with the air: after the use clean well by solvents the tools used.

Keep always the container well closed (keep open only the strictly necessary time to use the product).

Apply on porous surfaces, clean and dry, not polished but only grinded or rough. The product is not suitable for applying on low absorbing materials (polished marbles etc.). It is always suggested to effect a preliminary test to verify the compatibility of the product with the material.

Once completed the catalysis, it's very difficult to remove the protecting layer; for this purpose contact the manufacturer.

PACKAGING

1 L., 5 L., 10 L.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory test. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

A PRELIMINARY TEST ON A SMALL, HIDDEN, AREA IS ALWAYS RECOMMENDED BEFORE THE APPLICATION