



UNI EN ISO 9001:2008
Quality System Certified Company



TECHNICAL DATA SHEET

PRODUCT

KD 32 ZERO SOLVENTI

**REVIVING and PROTECTING AGENT
WATER BASE, SOLVENT FREE, for
MARBLE, GRANITE, NATURAL STONE
not polished**



Solvent free aqueous emulsion based on polymers that penetrate into the porosities of the treated material and develop a valuable "wet effect" that revives, in a totally natural way, the aspect of the material. It's environmentally friendly. It doesn't turn yellow

KD 32 ZERO SOLVENTI saturate the porosities of the treated material reducing the penetration of dirt and dust but keeping unchanged the natural transpiration of the treated surfaces. It is suitable for indoor and outdoor application, also on humid surfaces.

FUNCTION

Revives and protects the treated materials.

Enhances the shade of any natural stone evidencing the veins of the material.

LINE

PROTECTION

PROFESSIONALE

INDICATION

Revives the natural colours and develops a protecting effect of the treated materials

MATERIALS

For not polished and absorbing materials: marbles, granites and natural stones in general. It's specially suitable for coloured and polychrome materials.

HOW TO USE

Preparation of the surfaces. The surfaces must be clean, dry (also humid) and without trace of oily and greasy substances, alien substances and friable parts..

Application. Apply by using a clean cotton cloth or a tampon. Wait the product penetrates into the porosity of the material and rub to favour the even absorption of the product and to avoid the accumulating on the surface of not absorbed product.

To intensify the required effect, before the product dries on the surface, a second coat can be applied on the still humid surface (to favour the penetration of the product).

Attention. A preliminary test in a small part of the surface it is always recommended to evaluate, after drying, the compatibility of the product with the material and the obtained effect.

Important. The protecting effect is totally developed 24 hours after the final application.

When applied outdoor, avoid to apply on very hot surfaces because exposed to the sun; apply when the surface is cooled.

Do not apply in case of forthcoming rains to avoid the product is washed off before it is cured.

TEST

Effect always a test on a small part of the surface to determine the compatibility of the product with the material, the consumption, the drying time and, after drying, the aesthetic effect obtained and protection degree.

COMPOSITION

Aqueous emulsion of polymers

TECHNICAL DATA

Average drying time : 20 to 60 minutes (according to the environmental conditions)

Estimated consumption: 150-400 g/m² (according to the porosity and absorption of the material)



STABILITY

The product is an aqueous emulsion: CANNOT STAND THE FROST

Avoid the storage at temperatures lower than +5°C (41°F) or higher than +35°C (95°F)

PACKAGING

Plastic cans of 1L., 5L., 10L.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory test. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

A PRELIMINARY TEST ON A SMALL, HIDDEN, AREA IS ALWAYS RECOMMENDED BEFORE THE APPLICATION