



UNI EN ISO 9001:2008
Quality System Certified Company



TECHNICAL DATA SHEET PRODUCT

KR 33

**REVIVER OF THE NATURAL COLOUR
WATER REPELLENT SEALER**

KR 33 is an extremely versatile protective formula, solvent based, allowing a high penetration capacity into the material in depth. KR 33 has a pleasant reviving effect of the natural colours/shades ("wet effect") of the treated materials as well as an excellent waterproofing capacity thanks to the presence of organ-silicon compounds.

It is a sealer of long-lasting effects without making film on surface so keeping unchanged the natural transpiration capacity of the treated material.

FUNCTION

SEALER, WATER REPELLENT, REVIVER OF THE NATURAL COLOUR FOR POLISHED MARBLE AND GRANITE (not rough or flamed or unfinished)

LINE

PROTECTION

PROFESSIONAL

INDICATION

Makes water- and dirt-repellent the treated surfaces. Revives the natural colour, leaving the surface uniformly glossy, without changing the colour and the physical properties of the material. It doesn't anyway protect against acid substances.

MATERIALS

All absorbing natural stone: polished granites and marbles

Do not use on white or light crystalline marble (for these marbles, Ever Clean and Imperston are suggested)

USAGE

Apply undiluted to dry and clean surfaces with a brush or cotton cloth and let the material impregnate according to the porosity. For very porous materials, after drying, may be necessary to repeat the application.

Important: Do not leave excess of product dry on surface. Remove the excess of product with a clean (and possibly white) cotton cloth.

TEST

Testing a small, hidden area is recommended before application to determine consumption, drying time and to verify appearance and protection degree.

COMPOSITION

Contains silicon compounds and solvents

TECHNICAL INFORMATION

Evaporation time of solvent 20-40 minutes (depending on ambient conditions).

Consumption: 50 to 200 g/m² (3,5 to 10,5 oz/y²) depending on porosity

NOTE

Solvent-based product: inflammable. Apply in well ventilated areas while wearing impermeable gloves. For more information about safety, see product label or the Material Safety Data Sheet. Keep out from the reach of children



IMPORTANT

Apply to completely dry, clean and free from greasy substances surfaces.

Apply on polished materials (not rough or flamed).

Do not use on white or on very light colour or on crystalline marbles; in this case **Imperston** or **Ever Clean** must be used.

Protection capacity is fully operative after 18 to 24 from the application, depending on environmental conditions (temperature, humidity, ventilation, etc.)

PACKAGING

250 ml., 1 L., 5 L., 10L.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION