



UNI EN ISO 9001:2008  
Quality System Certified Company



## TECHNICAL DATA SHEET

PRODUCT

# OLDER 2.0

## zero solvents



**SHADE ENHANCER, REVIVER  
PROOFING  
WATER BASE  
FOR MARBLE AND NATURAL STONES**



Aqueous micro-dispersion of polymers that penetrate into the porosities of the treated material, proofing it and developing a "wet effect" that enhances the veins of the polychrome marbles and stones evidencing a revived natural and warm effect. It doesn't contain solvents and is environmentally friendly. Applicable both indoor and outdoor also on humid surfaces. Easy to apply, it saturates the porosities of the materials and reduce the penetration of dust and dirt, but leaving practically unchanged the natural transpiration of the treated materials.

### FUNCTION

Revives, strengthens and proofs the treated materials. Develops a warm and long lasting shade on all the natural stones evidencing the veins of the materials

### LINE

PROTECTION

PROFESSIONAL

### INDICATION

Revives the natural colours and develops a waterproofing and anti-dirt protecting effect.

### MATERIALS

Absorbing materials. Specially suitable for colour and polychrome marbles, it is also suitable for all kind of porous colour stones, not polished.

### HOW TO USE

**Preparation of the surface.** The surfaces must be clean, dry (even slightly humid) and free from any trace of oily and greasy substance, alien substances and friable parts.

**Application.** Apply by using a cotton cloth or a tampon. Wait the product penetration inside the porosities of the material, so rub softly in order to help and favour the homogeneous absorption and to avoid the accumulating of not absorbed product on the surface.

To intensify the effect, before the product dries on surface, it can be applied a second coat on the still humid material (to favour the penetration).

**Attention.** It is always recommended to effect a preliminary test on a small part of the surface and evaluate, after drying, the compatibility of the product with the material and the obtained effect.

**Important.** The strengthening and protecting effect is totally developed after 24 hours from the final application.

When applied outdoor, avoid the application on very hot surfaces/materials because exposed to the sun; apply when the surface is cooled. Do not apply in case of forthcoming rains to avoid the product is washed off before curing.

### TEST

Effect always a test on a small part of the surface to determine the compatibility of the product with the material, the consumption, the drying time and, after drying, the aesthetic effect obtained and protection degree.

### COMPOSITION

Aqueous emulsion of polymers.



### TECHNICAL DATA

Average drying time : 20 to 60 minutes (according to the environmental conditions)  
Estimated consumption: 150-400 g/m<sup>2</sup> (according to the porosity and absorption of the material)

### STABILITY

The product is an aqueous emulsion: CANNOT STAND THE FROST  
Avoid the storage at temperatures lower than +5°C (41°F) or higher than +35°C (95°F)

### PACKAGING

1L., 5L., 10L.

**LIMITATION OF LIABILITY** The data provided derive from published information or from our own laboratory test. The information provided here must be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

**A PRELIMINARY TEST ON A SMALL, HIDDEN, AREA IS ALWAYS RECOMMENDED BEFORE THE APPLICATION**