



TECHNICAL DATA SHEET PRODUCT

P F E

CLEANER FOR EPOXY FILLER/GROUTING

After filling the joints between tiles, this is the ideal product for removing the eventual residuals of epoxy filler/grouting. The product is very easy to use and highly versatile and can be applied on floors and walls of ceramics, grès porcelain tiles and on every kind of surface such as marbles, granites and natural stones both polished or not polished..

FUNCTION

CLEANING OF RESIDUALS OF GROUTINGS AND JOINT FILLERS

MATERIALS

CERAMICS, GRES PORCELAIN TILES, MARBLES, GRANITES, STONE MATERIALS IN GENERAL (polished or/and not polished)

DOSAGE

THE PRODUCT MUST APPLIED PURE WITHOUT ANY DILUTION.

HOW TO USE

APPLY ON THE AREA TO BE CLEANED AND RUB BY SPONGE OR COTTON CLOTH OR, IN CASE OF HARDENED RESIDUALS, BY PLASTIC BRUSH AND REMOVE FROM THE SURFACE ANY TRACE OF FILLING MADE BY EPOXY FILLER/GROUTING

COMPOSITION

CONTAINS PROPYLEN GLYCOL

TECHNICAL DATA

THE CONSUMPTION VARIES ACCORDING TO THE QUANTITY AND THE DRYING GRADE OF THE FILLER/GROUTING TO BE REMOVED.

STABILITY

Avoid the storage at temperatures lower than 5°C (41°F) or higher than 35°C (95°F).

NOTE

It is a chemical product: *keep out from the reach of children*

IMPORTANT

When using, it is suggested to wear impermeable gloves and safety goggles

PACKAGING

Can of 5 L. and 10 L.

LIMITED LIABILITY The information provided derives from bibliography or from our laboratory experience and should be understood as broad indications and not as a formal guarantee. In particular, the liability for defective products, once the defect has been ascertained, is limited to the product purchase price only. We do not undertake any liability for implicit or explicit damage due to use of the product beyond our direct control.

ALWAYS EFFECT A PRELIMINARY TEST BEFORE THE APPLICATION