



UNI EN ISO 9001:2008
Quality System Certified Company



TECHNICAL DATA SHEET PRODUCT

RAIN STOP C 70

WATER-REPELLENT, ANTISMOG, ANTIMOULD SEALER, WITH STRENGTHENING EFFECT

Ideal water repellent for interiors and exteriors. Solvent-based liquid formula recommended also for surfaces requiring higher resistance to alkaline environmental conditions. This solvent formula, easy to apply, (simply apply until no more product can be absorbed) allows a deep penetration. The product works by impregnation and doesn't form a film on the surface nor noticeably alter the original look of the surface. Before using the product, test the area to be treated, especially on particularly delicate materials, such as marble, sandstone and slate. RAINSTOP C 70 has also a long-lasting resistance to pedestrian traffic. The treated surfaces keep unchanged the natural capacity of transpiration of the material.

For highly absorbing materials a second coat after some hours may be needed.

FUNCTION IMPREGNATOR, WATER-REPELLENT, ANTISMOG, ANTIMOULD PROTECTING AGENT WITH STRENGTHENING EFFECT

LINE PROTECTION PROFESSIONAL

INDICATIONS Makes the surface water repellent without interfering with the natural transpiration of the material. It doesn't change the surface appearance. Water runs off without penetrating the surface. It doesn't anyway protect against acid substances.

MATERIALS MARBLE, GRANITE, NATURAL STONES, TERRAZZO and AGGLOMERATES etc. FOR FLOOR AND WALL APPLICATION. BOTH INDOOR AND OUTDOOR

HOW TO USE The surfaces to be treated must be clean, dry and free from any greasy or alien substance. Apply the undiluted product to the surface and let it penetrate according its porosity, but avoiding the drying of not absorbed excess of product. Remove any excess with a clean cotton cloth. After drying, in case of very absorbing materials of a second coat may be applied. On particularly delicate surfaces, slight modifications in colour (deepening) may occur. The user must effect own on-site testing to verify, after drying, the effect and the compatibility of the product with the material to be treated.

TEST On a small surface effect always a preliminary test to determine the compatibility between product and material, the consumption, the drying time and, after drying, the aesthetic result and the protection level effectively obtained.

COMPOSITION Contains silicon compounds and solvents

TECHNICAL INFORMATION Consumptions depend on the porosity of the material and is considered to be 100 to 250 gr/m². The solvent dries in 30-60 minutes depending on temperature, humidity, ventilation, etc. The proofing protection is fully effective 24 hours after the application.

NOTE Solvent-based product: flammable. Wear impermeable gloves, safety goggles and apply in well ventilated areas (eventually wear a solvent-proof mask). For more information, see the product label or the Material Safety Data Sheet.

IMPORTANT Apply to completely dry and clean surfaces. **DO NOT EFFECT THE APPLICATION WHEN STRONG SUN OR AT TEMPERATURES HIGHER THAT 25°C (77°F)** (APPLY WITH LOWER TEMPERATURE FOR A BETTER PENETRATION).

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Since the application of the product is beyond the control of the manufacturer or supplier, our liability for defective products, when verified, is limited to refund of the purchase price

A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION