



UNI EN ISO 9001:2008  
Quality System Certified Company



## TECHNICAL DATA SHEET PRODUCT

# REVSTONE L'ANTICO

**OIL and WATER REPELLENT  
with INTENSE REVIVING and ANTIQUING EFFECT**

REVSTONE L'ANTICO is the ideal product giving intense and longlasting "wet effect" and enhancing the veins of any kind of porous stone, it tones down light defects that may be found also in the most precious natural stones, marbles, granites. If the aesthetic aspect seems immediately as the main property of the product, not less important and of very good level is the oil and water repellent protection capacity that makes the treated surfaces anti-stain, easy to clean and with quite good anti-graffiti properties. The treatment of the surfaces, strictly effected according to the instructions of the technical data sheet, preserve and keep longer the beauty and preciousness of the material during the time..

### FUNCTION

PERFORMS A LONGLASTING AND PLEASANT "WET EFFECT"  
LASTINGLY REVIVES AND PROTECTS E PROTEGGE THE TREATED SURFACES

### LINE

PROTECTION

PROFESSIONAL

### INDICATION

MAKES A STABLE ANTI-DIRTY LAYER, CLUNG TO THE PORES OF THE MATERIAL, THAT REVIVES AND ENHANCES THE COLOURS

### MATERIALS

SUITABLE TO ALL KIND OF STONE AND POROUS MATERIAL AND PARTICULARLY SUITABLE FOR FLAMED, BRUSHED, GRINDED, SANDBLASTED STONES..

TONING COMPOUND: **NOT SUITABLE FOR WHITE OR VERY LIGHT MATERIAL.**

### HOW TO USE

**NEVER POUR DIRECTLY THE PRODUCT ON THE SURFACE TO BE TREATED** TO AVOID STAINS DUE TO AN IRREGULAR ABSORPTION, BUT APPLY ON CLEAN, ABSORBING AND DRY SURFACES BY USING A TAMPON OR A CLEAN COTTON CLOTH. RUB TO FAVOUR THE PENETRATION OF THE PRODUCT AND TO REMOVE ANY EXCESS OF PRODUCT. AVOID THE PRODUCT DRIES AND ACCUMULATE ON THE SURFACE.

IN CASE OF PRODUCT IN EXCESS RUB WELL WITH A DRY AND CLEAN COTTON CLOTH.

**DO NOT WALK ON THE SURFACE BEFORE DRYING** (THE DRYING IS COMPLETED 24 HOURS AFTER THE APPLICATION).

**REVSTONE L'ANTICO** IS READY TO USE BUT VERY CONCENTRATED AND GENERALLY A SECOND COAT IS NOT NEEDED.

APPLY ALWAYS A LIMITED QUANTITY OF PRODUCT AND EVALUATE AFTER 24 HOURS IF FURTHER INTENSIFICATION IS NEEDED.

TO OBTAIN THE BEST EFFECT IT IS POSSIBLE, AFTER DRYING, THE POLISHING OF THE SURFACE BY A SINGLE-BRUSH MACHINE FITTED OUT WITH POLISHING FELT.

ANYWAY IT IS SUGGESTED TO EFFECT A PRELIMINARY TEST ON A SMALL PART OF THE SURFACE FOR EVALUATE, AFTER DRYING, THE OBTAINED EFFECT.

### TEST

On a small surface effect always a preliminary test to determine consumption, drying time, compatibility between product and material and, after drying, the aesthetic result

### COMPOSITION

MIXTURE OF NATURAL AND SYNTHETIC COMPOUNDS IN ORGANIC SOLVENTS.

### TECHNICAL DATA

EVAPORATION TIME OF THE SOLVENT: 20 - 60 minutes (according to the environmental conditions).

AVERAGE CONSUMPTION: 100 to 200 grams per square metres (according to the material porosity)

### NOTE

SOLVENT BASE PRODUCT. IT IS SUGGESTED TO WEAR IMPERMEABLE GLOVES AND TO APPLY IN WELL AIRED ROOMS. FOR MORE INFORMATION ABOUT SAFETY, CONSULT THE MATERIAL SAFETY DATA SHEET.



## **IMPORTANT**

THE SURFACES TO BE TREATED MUST BE ABSORBING, CLEAN AND DRY.

NEVER POUR THE PRODUCT DIRECTLY ON THE SURFACE, BUT SPREAD THE PRODUCT BY CLEAN TAMPON OR COTTON CLOTH ONLY

ELIMINATE THE EXCESS OF PRODUCT BEFORE IT DRIES ON THE SURFACE.

SOLVENT BASE PRODUCT: PROTECT THE EYES AND THE FACE, AVOID THE CONTACT WITH THE SKIN, KEEP OUT FROM THE REACH OF CHILDREN

## **PACKAGING**

1 L., 5 L., 10 L.

### **LIMITATION OF LIABILITY**

The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Since the application of the product is beyond the control of the manufacturer or supplier, our liability for defective products, when verified, is limited to refund of the purchase price

**A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA ALWAYS IS RECOMMENDED BEFORE THE APPLICATION**