



UNI EN ISO 9001:2015
Quality System Certified Company



TECHNICAL DATA SHEET PRODUCT

SUPER BINDER 211



PROTECTION AGAINST THE RISING UP OF HUMIDITY and for IMPROVING THE ADHESION

SUPER BINDER 211 is suitable to be used as sealer for protection against the rising of the damp, that applied undiluted with a paint-brush immediately before laying on the back of the tile to lay. It is very efficacious against the ascending humidity and the rising up of stains from the support.

SUPER BINDER 211 is highly recommended to be used for laying absorbing and highly porous stone materials (marble, granite, natural stones) and of light colour stone materials such as Carrara White, Botticino, Thassos, Portugal Pink, etc.

Improves the adhesion between the materials and the laying bed (concrete mortar or cement powder adhesive).

FUNCTION

PROTECTION AGAINST THE RISING UP OF HUMIDITY and IMPROVEMENT OF THE ADHESION POWER

LINE

CONSTRUCTION

PROFESSIONAL

INDICATION

TO PROTECT AGAINST THE RISING UP OF HUMIDITY AND TO IMPROVE THE ADHESION.
SUITABLE FOR MATERIALS LAID BOTH INDOOR AND OUTDOOR

MATERIALS

MARBLES, GRANITES, NATURAL STONES, TERRACOTTA.

HOW TO USE

THE PRODUCT IS READY-TO-USE. APPLY THE UNDILUTED PRODUCT BY PAINT-BRUSH ON THE BACK OF THE TILES OR MATERIALS AND LAY IMMEDIATELY THE PIECE. DON'T LET IT DRY ON THE BACK OF THE PIECE.
APPLY AT TEMPERATURE NOT LOWER THAN 5°C (41°F) BUT NOT HIGHER THAN 35°C (95°F)

TEST

Before the application, always effect a preliminary test to verify the compatibility of the product with the materials used.

COMPOSITION

ANIONIC MICRONIZED EMULSION OF COPOLYMER

CONSUMPTION

100 - 150 grams/sq.m. ACCORDING TO THE KIND OF MATERIAL (absorption, porosity, etc.)

STABILITY

TO PRESERVE THE PRODUCT WELL, KEEP THE CONTAINER TIGHTLY CLOSED TO AVOID THE WATER EVAPORATION AND THE MAKING OF THE SURFACE FILM. KEEP INTO THE SEALED ORIGINAL CONTAINERS AND SHELTERED FROM TEMPERATURES LOWER THAN 5°C (41°F) OR HIGHER THAN 35°C (95°F).

PROTECT FROM THE FROST.

THESE CONDITIONS RESPECTED, THE EMULSION IS STABLE 12 MONTHS AT LEAST.



SAFETY

UNDER NORMAL CONDITIONS OF USE, THE PRODUCT IS NOT HAZARDOUS AND IT IS NOT CLASSIFIED AS HAZARDOUS MATERIAL ACCORDING TO THE EU STANDARD

PACKAGING

5 L., 10 L., 20 L.

LIMITED LIABILITY The information supplied has been taken from the bibliography and from our laboratory experience and is to be understood as general indications and not a formal guarantee. In particular, responsibility for defective products, when ascertained, is limited to the product purchase price. The manufacturer cannot be held responsible for any implicit or explicit damages due to use of the product which remains beyond our direct control.

ALWAYS MAKE A PRELIMINARY TEST BEFORE THE FINAL APPLICATION